Appln. No. 10/788,621

Attorney Docket No. DKT03160

I. Listing of Claims

1. (Currently Amended): A unitary electrohydraulic clutch assembly comprising, in combination,

an input member and a coaxially disposed output member defining an axis,

a bi-directional electric motor having an output hub,

means for inhibiting back driving of a said electric motor associated with said output hub and having an output,

a gear train having an input driven by said inhibiting means output and an output,

a ball screw driven by said gear train output and driving a first piston displacing hydraulic fluid,

an annular piston disposed on said axis and translated by said hydraulic fluid, and

a friction clutch pack disposed on said axis and operably disposed between said input member and said output member and actuated by said second annular piston.

- 2. (Cancelled).
- (Previously Presented): The electrohydraulic clutch assembly of claim
 wherein said inhibiting means includes a wrap spring disposed within a cylindrical passageway and extending between said output hub and said inhibiting means output.

-2-

12/27/2005 17:18 FAX 17349946331

BRINKS.HOFER.ET AL

2004

Appln. No. 10/788,621

Attorney Docket No. DKT03160

 (Original): The electrohydraulic clutch assembly of claim of 1 further including a pressure sensor for providing a signal representing a pressure of

hydraulic fluid generated by said first piston.

5. (Original): The electrohydraulic clutch assembly of cla m 1 further

including a microprocessor having an output adapted to bi-directionally drive said

electric motor.

6. (Original): The electrohydraulic clutch assembly of claim 1 wherein

said friction clutch pack includes a first plurality of clutch plates coupled to said input

member and a second plurality of clutch plates interleaved with said first plurality of

clutch plates and coupled to said output member.

7. (Original): The electrohydraulic clutch assembly of claim 1 further

including a circular apply plate and a thrust bearing both disposed between said

second piston and said friction clutch pack.

8. (Currently Amended): A unitary electrohydraulic clutch assembly

comprising, in combination,

an input shaft and a coaxially disposed output shaft defining an axis,

an electric motor,

a gear train for reducing an output speed of said electric motor,

means for inhibiting back driving of said electric motor operably disposed

between said motor and said gear train,

-3-

12/27/2005 17:18 FAX 17349946331

BRINKS, HOFER, ET AL

Ø 005

Appin. No. 10/788,621

Attorney Docket No. DKT03160

a master piston,

a rotary motion to linear motion transducer driven by said gear train and

driving said master piston,

a friction clutch pack operably disposed between said input shaft and said

output shaft including first and second interleaved pluralities of clutch plates

disposed on said axis, and

an annular slave piston in fluid communication with said master piston,

disposed on said axis and acting upon said friction clutch pack.

9. (Cancelled).

10. (Cancelled).

11. (Original): The electrohydraulic clutch assembly of claim of 8 further

including a pressure sensor for providing a signal representing a pressure of

hydraulic fluid generated by said master piston.

12. (Original): The electrohydraulic clutch assembly of claim 8 further

including a microprocessor having an output for bi-directionally driving said electric

motor.

13. (Previously Presented): The electrohydraulic clutch assembly of claim

8 wherein said first plurality of clutch plates is coupled to said input shaft and said

second plurality of clutch plates is coupled to said output shaft.

-4-

Appln. No. 10/788,621

Attorney Docket No. DKT03160

14. (Original): The electrohydraulic clutch assembly of clam 8 further including a circular apply plate and a thrust bearing both disposed between said slave piston and said friction clutch pack.

15. (Currently Amended): A unitary electrohydraulic clutch assembly for motor vehicle drivelines, comprising, in combination,

a bi-directional electric motor having an output hub,

a wrap spring disposed within a cylindrical passageway and extending between said output hub and a drive pinion.

a gear train having in input driven by said drive pinion and an output, said gear train having at least two pinion gears and two, larger spur gears,

a ball screw assembly driven by said output of said gear train,

a first piston bi-directionally translated by said ball screw assembly,

an annular piston in fluid communication with said first piston,

a friction clutch pack having an input and an output and acted upon by said second annular piston, and

a circular apply plate and a thrust bearing both disposed between said annular piston and said friction clutch pack.

16. (Cancelled).

17. (Cancelled).

-5-

BRINKS, HOFER, ET AL

12/27/2005 17:18 FAX 17349946331

Ø 007

Appln. No. 10/788,621

Attorney Docket No. DKT03160

18. (Currently Amended): The electrohydraulic clutch asserbly of claim

[[17]] 15 wherein said drive hub and said driven pinion include a coupling

accommodating limited relative rotation.

19. (Original): The electrohydraulic clutch assembly of claim of 15 further

including a pressure sensor for providing a signal representing a pressure of

hydraulic fluid generated by said master piston.

20. (Original): The electrohydraulic clutch assembly of claim 15 further

including a microprocessor having an output adapted to bi-directionally drive said

electric motor.

21. (Original): The electrohydraulic clutch assembly of claim 15 wherein

said friction clutch pack includes a first plurality of clutch plates coupled to said input

member and a second plurality of clutch plates interleaved with said first plurality of

clutch plates and coupled to said output member.

22. (Original): The electrohydraulic clutch assembly of claim 15 wherein

said output of said friction clutch pack provides drive torque to a differential in a

motor vehicle driveline.

23. (Cancelled).

Please add the following new claims.

-6-

Appin. No. 10/788,621

Attorney Docket No. DKT03160

24. (New): The electrohydraulic clutch assembly of claim 1 further including a housing configured to receive said input member, said output member, said electric motor, said back drive inhibiting means, said gear train, said ball screw assembly, said pistons and said friction clutch pack.

25. (New): The electrohydraulic clutch assembly of claim 8 further including a housing configured to receive said input member, said out; out member, said electric motor, said back drive inhibiting means, said gear train, said ball screw assembly, said pistons and said friction clutch pack.

26. (New): The electrohydraulic clutch assembly of claim 15 further including a housing configured to receive said input member, said output member, said electric motor, said back drive inhibiting means, said gear train, said ball screw assembly, said pistons and said friction clutch pack.